

OD (in): 3.500

WT (in): 0.254

ID (in): 2.992

Drift (in): 2.867

---

Grade: L-80

Yield Strength min (lbs): 207,200

Internal Yield Pressure (psi): 10,160

Collapse Resistance (psi): 10,540

---

Connection

Critical Section Area (in<sup>2</sup>): 1.29

Connection ID (in): 2.92

Minimum Parting Load (lbs): 125,000

Compressive Limit (lbs): 125,000

Tension Efficiency: 60%

Compression Efficiency: 60%

Maximum Bend (°/100ft): 63

---

Operational Data

Nominal Torque Shoulder (ft\*lbs): 725

Maximum Setting Depth (ft): 8,800

Minimum Makeup Torque (ft\*lbs): 1,700

Safety Factor: 1.6

Optimum Makeup Torque (ft\*lbs): 2,400

Maximum Yield Torque: 2,800

Makeup Loss (in): 2.860

- 
- True ID / OD flush, gas-tight connection.
  - Axial metal to metal nose seal with internal & external torque shoulder.
  - Large torque shoulders to allow for high torque values.
  - 90° load flank with large-radius stab flank.
  - Excellent for slim hole applications and well bore reconstruction.



Disclaimer:

LFS is a registered trademark to LFS Technologies Inc. The content of this Technical Data Sheet is for general information only and does not guarantee performance or imply fitness for a particular purpose. This material should not, therefore, be used or relied upon for any specific application without independent competent professional examination and verification of its accuracy, suitability and applicability. Anyone making use of the material does so at their own risk and assumes any and all liability resulting from such use.